

Application data sheet Shefcut® Precision Reaming & Boring Solutions

products, inc.

CUSTOMER		DATE	PLEASE
ADDRESS			РНОТОСОРУ
CITY	STATE	ZIP	& COMPLETE THIS FORM &
CONTACT	TITLE		
PHONEFAX	E-MAIL		WITH YOUR ORDER OR
SALES AGENT/DISTRIBUTOR	SALESMAN		
PART NUMBER AND DESCRIPTION			FOR
QUOTING QUANTITY		PRINTS INCLUDED YES 🖵 NO	QUOTATION. THE DATA
B/P DRAWING NO			WILL BE USED
PRIMARY OBJECTIVE SIZE FINISH BORE LOCATION OTHER			TO ENSURE THAT THE
EXACT BORE SIZE(S) REQUIRED/TOLERANCES		ROUNDNESS TOLERANCE	
STRAIGHTNESS TOLERANCE	SURFACE	FINISH REQUIRED	TOOL IS FURNISHED
MATERIAL TYPE & SPECIFICATIONS	PE & SPECIFICATIONSHARDNESS OR TENSILE STRENGTH FOR YOUR PARTICULAR		
PRE-REAMED DIAMETER(S)/MACHINING ALLOWANCE			
LENGTH OF BORE(S)			
AT TIME OF SHEFCUT OPERATION IS IT A THROUGH OR BLIND HOLE (Circle one)			
IS BORE INTERRUPTED? YES INO IN (If yes, or if blind hole, include sketch of bore or part print)			NOTE: For all
MACHINE TYPEHORIZONTAL OR VERTICAL?			values expressed,
IS A FIXED OR ROTATING BUSHING IN USE?			please indicate
EXPECTED PART TO SPINDLE ALIGNMENT		MACHINE SET-UP: RIGID 🖵 FLOATING 🕻	whether metric or inch.
FEED RANGE AVAILABLE	SPEED RANGE AVAILABLERPM		M or mon.
TYPE OF SHANK REQUIREDMAXIMUM TOOL PROJECTION FROM SPINDLE			_
	WORK LENGTH REQUIRED		
IF THERE IS A WEIGHT LIMIT, PLEASE SPECIFY		USED IN A TOOL CHANGER? YES 📮 NO	<u> </u>
TYPE OF COOLANT LUBRICATION DESIRED: INTERNAL THROUGH THE SPINDLE INTER	RNAL ROTARY GLAND 🖵	EXTERNAL FLOOD 🖫	
NAME AND TYPE OF COOLANT AVAILABLE:	STRAIGHT CUTTING OIL		
		DILUTION	
		DILUTION	
COOLANT PRESSURE	COOLANT FLOW		
WILL THE TOOL BE: ROTATING STATIONARY			
PRODUCTION REQUIREMENT			_
ADDITIONAL COMMENTS			_

Fax or mail to:

FAX (803) 438-5263 Cogsdill Tool Products, Inc. P.O. Box 7007 Camden, SC 29021 ATTN: CUSTOMER SERVICE

